

# Technical Data Sheet



## *Patch*

<i>Input</i>	<i>Instrument</i>	<i>Microphone</i>	<i>Insert (F.O.H)</i>
1	Bass drum	AKG D112	Gate + Comp
2	Snare top	SM 57	Comp
3	Snare bottom	BETA 57	Gate
4	Tom	e 604	Gate
5	Floor tom	MD 421	Gate
6	Hi hat	Condenser	
7	Overhead right	Condenser	
8	Overhead left	Condenser	
9	Bass DI	Active DI	Comp
10	Bass mic	MD 421	Comp
11	Guitar 1	SM 57 or MD 441	
12	Guitar 2	SM 57 or MD 421	
13	Lead vocals	Beta 58	Comp
14	Backing vocals	Beta 58	Comp
15	Backing vocals	Beta 58	Comp
16	Backing vocals	Beta 58	Comp

## *FOH Technical Data*

Indoor venues +/- 15w p/person - outdoor venues +/- 25w p/person

3 ways stereo system (EAW-Nexo-Martin-...) with a graphic EQ 2\*31bands

24/8 professional mixing desk (Midas-Allen&Heat-Yamaha-...) + 1 CD player

## *Group or VCA*

1-2 Drum 2 linked compressors

3-4 Bass

5-6 FX (1 reverb room, 1 reverb plate and 1 delay with tap tempo controller)

## *Monitors Technical Data*

6x 1kW wedges with 4\*32 bands EQ place such as on the stage map (\*)

and similar monitor for the monitor engineer's wedge

*HF System headphone for the drummer* (if possible)

\* Available on the second sheet